



Science.
Applied to Life.™



Help Protect against Graffiti

Whether applied to windows or mirrored surfaces, such as in transit stops, bathrooms or retail displays, 3M™ Anti-Graffiti Window Films help provide a strong first line of defense against vandalism, graffiti, etching, scratches, and abrasion. If damage is done, these removable films allows you to simply replace the film for a fraction of the cost.

- ▶ Surface protection against most scratches, acid etching, gouges and tagging
- ▶ The sacrificial film is easy to remove and replace
- ▶ A fraction of the cost of new glass



Events and Seasonal Tourism

On glass graffiti occurring during peak sales opportunities, such as events and seasonal tourism, not only damages your image but may deter limited-time customers from giving your store a chance. Glass replacement would be costly and more disruptive, while 3M™ Anti-Graffiti Film can be removed and replaced quickly, and without the need to remove your windows.



Maintaining Your Image

When you see a building with graffiti or scratches on the window, what do you immediately think about that building or part of town? Your store is your livelihood. Do not let future customers have that opinion about your business. Protect your windows with 3M™ Anti-Graffiti Film so that signs of vandalism can be removed quickly, which can help you maintain your valued reputation.



Civil Unrest

During times of civil unrest, large groups of passionate individuals can quickly generate graffiti or other glass surface damage. Use 3M™ Anti-Graffiti Film to help protect your windows from tagging or etching. Damaged glass is very expensive to replace. Don't replace the entire window when you can simply replace a cost-effective film layer: 3M™ Anti-Graffiti Film.



Product Properties

Film Properties* (nominal)	AG-4	AG-6
Film Thickness	≥0.004"	≥0.008"
Tensile Strength	>25,000 psi	>25,000 psi
Break Strength	136 lbs/in	150 lbs/in
Elongation at Break	>100%	>100%
Peel Strength	1 lb/in	1 lb/in
Puncture Strength	90 lbs	125 lbs
Abrasion Resistance	<5% increase in haze	<5% increase in haze

*Film properties not for specification purposes.

3M.com/WindowFilm.

IMPORTANT: This is an overview of product features and benefits. Prior to product selection, always refer to the current 3M Technical Data Sheet and 3M Technical Specifications for more detailed product information

Warranty, Limited Remedy, and Disclaimer: Please refer to the Warranty Bulletin for 3M™ Window Films (Flat Glass Applications) and 3M™ Impact Protection Attachment (IPA) Sealant for complete details on warranty coverage, which can be obtained by contacting your 3M Authorized Window Film Dealer or your local 3M sales representative. If a 3M product does not conform to the warranties described in this Warranty Bulletin, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



3M Commercial Solutions Division
3M Center, Building 223-3N-30
St. Paul, MN 55144-1000
3M.com/windowfilm

3M is a trademark of 3M.
Used under license in Canada.

Please recycle. Printed in the U.S.A.
© 3M 2024. All rights reserved.
98-0150-0726-7